

## File 2/2H system - Reglette LED 24W/m

code R182M0.840D



### PRODUCT DESCRIPTION

Modular system for direct, diffused and/or accent lighting, consisting of hollow profiles made from 75x78 mm painted or anodised extruded aluminium, with a predefined length or cut to measure, available in the following versions: wall-mounted, ceiling-mounted, suspended, recessed with a super-slim edge trim, just 5 mm wide, and trimless, fully-retracting flush recessed. To be integrated with LED linear light sources, battens for T16 and T16 seamless fluorescent lamps, recessed versions with built-in LED source or for QPAR16 halogen/LED lamps and max 16A 3-circuit track modules for inclusion of projectors. Fluorescent battens, complete with 50/60 Hz 230/240 V electronic power supply, LED batten driver included. To be completed with side end caps with Light Proof system, opal white or microprismatic PC diffusing screen (in accordance with EN 12464-1), closing profiles, with a predefined length or cut to measure, or darklight aluminium grille with high specular qualities and mounting brackets or suspension cables. IP20/IP40 protection rating.

### PRODUCT SPECS

|                              |                       |
|------------------------------|-----------------------|
| Installation method          | system                |
| Light source                 | LED                   |
| Absorbed power               | 12,8 W                |
| Color temperature            | 4000K                 |
| Color rendering index CRI    | >90                   |
| Luminous flux of the product | 2044 lm               |
| Luminous efficiency          | 160 lm/W              |
| MacAdam color tolerance      | 3                     |
| Life time estimate           | 50000h Ta 25° L80 B10 |
| Protocol                     | Dimmable Dali         |
| Energy efficiency class      | E                     |
| Dimension                    | L560 mm               |
| IP Grade                     | IP20                  |
| Power supply                 | 220-240V 50-60Hz      |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.  
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.  
We reserve the right to make changes to our products at any time.

Page 1 / 1