

## File 2 Ceiling Ip54 LED A/F

code F2253.940X/01



### PRODUCT DESCRIPTION

Ceiling luminaire IP54 outdoor, direct and diffused light. Body in extruded aluminum 6060, head in die-cast aluminum light proof, led SMD professional 32W/mt color temperature 4000K, assembled on rigid pcb with spray coating treatment for moisture protection, mounted and wired on ARS1 anodized aluminum extruded heatsink with additional transparent palsun protection to prevent contact to the LEDs during installation or maintenance, quick installation tools free by means of Click system with double-click harmonic steel springs for a first clamping to the profile that allows the wiring to the electrical network, to quick coupling without using screws. Integrated electronic power supply.

### PRODUCT SPECS

|                              |                         |
|------------------------------|-------------------------|
| Installation method          | Ceiling surface mounted |
| Light source                 | linear LED 32W/mt CRI90 |
| Absorbed power               | 45 W                    |
| Color temperature            | 4000K                   |
| Color rendering index CRI    | 90                      |
| Optic                        | Microprismatic diffuser |
| Finishing                    | White                   |
| Luminous flux of the product | 3704 lm                 |
| Luminous efficiency          | 82 lm/W                 |
| Protocol                     | On/Off                  |
| Energy efficiency class      | D                       |
| Dimension                    | L1420 mm                |
| Power supply                 | 220-240V 50-60Hz        |

### WEB PAGE

