

## File 2 track 32W/m

code F2533.940XD/01



### PRODUCT DESCRIPTION

Direct light indoor track lamp made of extruded aluminum 6060; complete with LED; color rendering index CRI>90. Protocol Dimmable Dali; lamp with colour finish white; in polycarbonate with diffusing film. Protection rating IP40/IP43. Can be installabile on most tracks 3 phases in trade the product in white and oxised silver mount a white track adapter. The product in black, oxised inox, moka mount a black track adapter. For connection to theOne Track (A.A.G. Stucchi ) or Global Track pulse (Nordic Aluminium).

### PRODUCT SPECS

|                              |                                         |
|------------------------------|-----------------------------------------|
| Installation method          | Track                                   |
| Light source                 | linear LED 32W/mt CRI90                 |
| Absorbed power               | 45 W                                    |
| Color temperature            | 4000K                                   |
| Color rendering index CRI    | 90                                      |
| Optic                        | Microprismatic diffuser                 |
| Finishing                    | White                                   |
| Luminous flux of the product | 3704 lm                                 |
| Luminous efficiency          | 82 lm/W                                 |
| Protocol                     | Dimmable Dali                           |
| Energy efficiency class      | D                                       |
| Dimension                    | W1420 mm                                |
| IP Grade                     | Inst. Parete Ip40 / Inst. Soffitto Ip43 |
| Power supply                 | 220-240V 50-60Hz                        |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

