





## Microfile H Square Suspension

code MFH031.840/01



### PRODUCT DESCRIPTION

Suspended, recessed, wall/ceiling lighting fixtures in extruded aluminum for direct or bi-emission diffused lighting of circular, square, rectangular or hexagonal shape complete with silicone screen. Integrated linear LED sources to be completed with 24Vdc remote power supply. IP44. Available default modules on demand and modular system.

### PRODUCT SPECS

|                              |                     |
|------------------------------|---------------------|
| Installation method          | Suspension          |
| Light source                 | Led                 |
| Absorbed power               | 78 W                |
| Color temperature            | 4000K               |
| Color rendering index CRI    | 80                  |
| Finishing                    | White               |
| Luminous flux of the product | 3476 lm             |
| Luminous efficiency          | 45 lm/W             |
| Energy efficiency class      | D                   |
| Weight                       | 3 Kg                |
| Dimension                    | L1200xW650 mm       |
| IP Grade                     | Ip44                |
| Protection Class             | Class III appliance |
| Product Spec                 | Square shape        |
| Power supply/Transformer     | Not included        |
| Protocol                     | See power supply    |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS



## OPTIONAL ACCESSORIES

### **Lbs System Canopy for housing driver**



code LB421/01

REGISTERED DESIGN - File Flex is a versatile extruded aluminium profile, which can design infinite shapes. Its asymmetrical section is designed to realize unique lighting effects meanwhile ensuring optimal illumination levels. The linear LED source screened by a flexible opal extruded silicone diffuser creates seamless lighting effects. The system allows the use of blind modules, multi-optic from Leva series or adjustable spot from Spot Focus series Ø26 and Ø36. It has to be completed by stabilized drivers 24V or 48V.

**Technical Sheet**



### **Lbs System Canopy for plasterboard false-ceiling**

Lbs System Canopy for plasterboard false-ceiling



code LB428/01

Lbs System Canopy for plasterboard false-ceiling

**Technical Sheet**

