


Leva 3 Outdoor Trimless Recessed - kit

code LV003P.935Z/01



PRODUCT DESCRIPTION

Luminaire for integrated LED Chip On Board sources. Flush-mounted installation. Luminaire body in extruded painted aluminium white. Optical groups complete with LED chip on board, lens, anti-glare housing. Optical 41°x18° UGR<16.

PRODUCT SPECS

Installation method	Trimless recessed
Light source	LED
Absorbed power	3x2,2 W
Color temperature	3500K
Color rendering index CRI	>90
Optic	Asymmetric 41°x18°
Finishing	White
Luminous flux of the product	708 lm
Luminous efficiency	107 lm/W
MacAdam color tolerance	2
Life time estimate	50000h Ta 25° L90B10
Energy efficiency class	E
Weight	0.06 Kg
Dimension	L90xW27xH60 mm
IP Grade	Ip56
Protection Class	Class III appliance
Product Spec	Rectangular shape
Power supply/Transformer	Not included
Protocol	See power supply



WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 3

MANDATORY ACCESSORIES

Box Leva 3 trimless



code LV003A

Trimless recessed uncategorized wallbox for false ceiling

Technical Sheet



OPTIONAL ACCESSORIES

Wallbox for brick wall and concrete – Leva3



code CCLV03

Formwork for masonry and concrete, suitable for Leva3. Internal length 97mm - external length 99,4mm

Technical Sheet



