

## Pro Edge system - spot Focus 55

code PE201.9HCS/01



### PRODUCT DESCRIPTION

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; precise photometric curve with different emission angles; optical units available as accessories with replacement without tools; hot plug protection; available accessories such as honey comb, ellipsoid lens, asymmetric lens, satined lens. Color finish white.

### PRODUCT SPECS

|                           |                                |
|---------------------------|--------------------------------|
| Installation method       | system                         |
| Light source              | LED                            |
| Absorbed power            | 12 W / 18 W                    |
| Color temperature         | Horticulture                   |
| Color rendering index CRI | >90                            |
| Optic                     | Spot 15°                       |
| Finishing                 | White                          |
| MacAdam color tolerance   | 2                              |
| Life time estimate        | 2SCDM 50.000h L90 B10<br>ta25° |
| Energy efficiency class   | D                              |
| Dimension                 | H125 Ø55 mm                    |
| IP Grade                  | IP20                           |
| Protection Class          | Class III appliance            |
| Power supply/Transformer  | Not included                   |
| Protocol                  | See power supply               |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS

