



## Pro Edge system - spot Focus 36

code PE200.935Z/01



### PRODUCT DESCRIPTION

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; precise photometric curve with different emission angles; optical units available as accessories with replacement without tools; hot plug protection; available accessories such as honey comb, ellipsoid lens, asymmetric lens, satined lens. Color finish white.

### PRODUCT SPECS

|                              |                             |
|------------------------------|-----------------------------|
| Installation method          | system                      |
| Light source                 | LED                         |
| Absorbed power               | 8 W                         |
| Color temperature            | 3500K                       |
| Color rendering index CRI    | >90                         |
| Optic                        | Asymmetric 18X28°           |
| Finishing                    | White                       |
| Luminous flux of the product | 517 lm                      |
| Luminous efficiency          | 65 lm/W                     |
| MacAdam color tolerance      | 2                           |
| Life time estimate           | 2SCDM 50.000h L90 B10 ta25° |
| Energy efficiency class      | D                           |
| Dimension                    | H85 Ø36 mm                  |
| IP Grade                     | IP20                        |
| Protection Class             | Class III appliance         |
| Power supply/Transformer     | Not included                |
| Protocol                     | See power supply            |

### WEB PAGE



### ASSEMBLY INSTRUCTIONS



