

**Pro Edge system - Spot Focus 90**

code PE204.930W/01

**PRODUCT DESCRIPTION**

Cylindrical projector in extruded aluminium, adjustable on the vertical axis of 355, and on the horizontal axis of +/- 90, equipped with hook for installation on the profile; powder coating; with COB technology (Chip on Board) for maximum efficiency; absence of multiple shadows; Energy efficient LEDs with high color rendering; secondary lens in high transparency pmma; precise photometric curve with different emission angles; optical units available as accessories with replacement without tools; hot plug protection; available accessories such as honey comb, ellipsoid lens, asymmetric lens, satined lens. Color finish white.

**PRODUCT SPECS**

|                              |                      |
|------------------------------|----------------------|
| Installation method          | system               |
| Light source                 | LED                  |
| Absorbed power               | 32 W                 |
| Color temperature            | 3000K                |
| Color rendering index CRI    | >90                  |
| Optic                        | Wide 38°             |
| Finishing                    | White                |
| Luminous flux of the product | 4960 lm              |
| Luminous efficiency          | 155 lm/W             |
| MacAdam color tolerance      | 3                    |
| Life time estimate           | 50000h Ta 25° L80B10 |
| Energy efficiency class      | E                    |
| Dimension                    | H110 Ø90 mm          |

**WEB PAGE****ASSEMBLY INSTRUCTIONS**

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 1