

Leva 3 Outdoor Recessed - kit

code LV003P..940S/01




PRODUCT DESCRIPTION

Integrated LED Chip On Board light fixture. Recessed installation with stop. Luminaire body in extruded painted aluminum white. Optical groups complete with LED chip on board, lens, anti-glare housing. Optics 20° UGR<16.

PRODUCT SPECS

Installation method	Recessed with frame
Light source	LED
Absorbed power	3x2,2 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Spot 20°
Finishing	White
Luminous flux of the product	615 lm
Luminous efficiency	93 lm/W
MacAdam color tolerance	2
Life time estimate	50000h Ta 25° L90B10
Energy efficiency class	E
Weight	0.06 Kg
Dimension	L90xW27xH60 mm
IP Grade	Ip56
Protection Class	Class III appliance
Power supply/Transformer	Not included
Protocol	See power supply



WEB PAGE



ASSEMBLY INSTRUCTIONS



MANDATORY ACCESSORIES

Box Leva 3



code LV003F/01

Recessed with frame uncategorized wallbox for false ceiling. Bianco finishing wallbox for false ceiling

Technical Sheet



AE700.10C



code AE700.10C

Electronic power supply current

IMMAGINE PURAMENTE DIMOSTRATIVA
PURELY DEMONSTRATION IMAGE

OPTIONAL ACCESSORIES

Wallbox for brick wall and concrete – Leva3



code CCLV03

Formwork for masonry and concrete, suitable for Leva3. Internal length 97mm - external length 99,4mm

Technical Sheet

