

File Suspension

code F1316.827PD/01



FILE opal LED



PRODUCT DESCRIPTION

Direct light indoor suspension lamp made of extruded aluminum 6060, complete with led; color rendering index CRI >90. Professional led 51.2 W modules assembled and wired on extruded aluminum heatsink with high performance reflector, equipped with harmonic steel springs for installation in the profile Tools free; wiring through 5 cables with quick coupling terminal blocks; protocol Dimmable Dali / Touch & Dimm. Lamp with color finish white; in polycarbonate with diffusing film. Degree of protection IP40/IP43.

PRODUCT SPECS

Installation method	Suspension
Light source	LED
Absorbed power	51,2 W / 22,5 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Opal polycarbonate diffuser
Finishing	White
Luminous flux of the product	2885 lm / 1308 lm
Luminous efficiency	56 lm/W / 58,13 lm/W
MacAdam color tolerance	3
Life time estimate	50000h Ta 25° L80B10
Protocol	Dimmable Dali / Touch & Dimm
Energy efficiency class	E
Weight	4.20 Kg
Dimension	L2265 mm
IP Grade	IP40
Power supply	220-240V 50-60Hz

WEB PAGE



ASSEMBLY INSTRUCTIONS

