

I-kone recessed frame fixed

code IK007.930W/01





PRODUCT DESCRIPTION

Recessed direct light lamp with circular stop complete with LED 12 W or 18 W secondary optical color white, color rendering index CRI92. Color finish white. Optical body made of die-cast aluminum, passive dissipation with black anodized aluminum heatsink high thermal efficiency. 99.9% aluminium finish optics, backlit light source with anti-glare effect; degree of protection IP20/23. Powder coating.

PRODUCT SPECS

Installation method	recessed with frame
Light source	LED
Absorbed power	12 W / 18 W
Color temperature	3000K
Color rendering index CRI	>90
Optic	Wide 46°
Finishing	White
Luminous flux of the product	1285 lm / 2358 lm
Luminous efficiency	107 lm/W / 131 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Weight	0.35 Kg
Dimension	H131 Ø88 mm
Hole size	Ø 80 mm
IP Grade	Inst. Parete Ip20 / Inst. Soffitto Ip23
Protection Class	Class III appliance
Power supply/Transformer	Not included
Protocol	See power supply



WEB PAGE



ASSEMBLY INSTRUCTIONS



