

I-SQUARE FRAME FIXED

code IS013.935F/01



250

350


















PRODUCT DESCRIPTION

Recessed direct light lamp with square-shaped indoor stop complete with LED 8 W or 12 W secondary optical color white, color rendering index CRI92. Color finish white. Optical body made of die-cast aluminum, passive dissipation with black anodized aluminum heatsink high thermal efficiency. 99.9% aluminium finish optics, backlit light source with anti-glare effect; degree of protection IP20/23. Powder coating.

PRODUCT SPECS

Installation method	recessed with frame
Light source	LED
Absorbed power	8 W / 12 W
Color temperature	3500K
Color rendering index CRI	>90
Optic	Flood 27°
Finishing	White
Luminous flux of the product	1089 lm / 1333 lm
Luminous efficiency	136 lm/W / 111 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Energy efficiency class	D
Weight	0.35 Kg
Dimension	L84.5x84.5xH95 mm
Hole size	77X77 mm
IP Grade	Inst. Parete Ip20 / Inst. Soffitto Ip23
Protection Class	Class III appliance
Product Spec	Square shape
Power supply/Transformer	Not included
Protocol	See power supply

WEB PAGE



MANDATORY ACCESSORIES

AE350.16C (Copia)



code AE350.15C

Electronic power supply current

AE500.20C1 (Copia)



code AE500.20C.MP

Electronic power supply current

