


## **Best minimal fixed**

code BT752.935WL/01





















## PRODUCT DESCRIPTION

Trimless direct fixed recessed light, indoor, circular shape complete with high efficiency COB LED, CRI>90 polycarbonate secondary optics. Colour body white complete with . Optical body made of die-cast aluminum, passive dissipation with black anodized aluminum heatsink high thermal efficiency. Optical group removable from the ring that is fixed and grouted in plasterboard. Degree of protection IP20/23. Powder coating.

## **PRODUCT SPECS**

Installation method	Trimless recessed
Light source	LED
Absorbed power	12 W
Color temperature	3500K
Color rendering index CRI	>90
Optic	Wide 38°
Finishing	White
Luminous flux of the product	1560 lm
Luminous efficiency	130 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Life time estimate  Energy efficiency class	
	ta25°
Energy efficiency class	ta25° D
Energy efficiency class Weight	ta25° D 0.49 Kg
Energy efficiency class Weight Dimension	ta25° D 0.49 Kg L75xH100 Ø83 mm
Energy efficiency class Weight Dimension Hole size	ta25° D 0.49 Kg L75xH100 Ø83 mm Ø 75 mm Inst. Parete Ip20 / Inst.
Energy efficiency class Weight Dimension Hole size IP Grade	ta25° D 0.49 Kg L75xH100 Ø83 mm Ø 75 mm Inst. Parete Ip20 / Inst. Soffitto Ip23

## **WEB PAGE**



