

**Mini Track - IPipedi 55/300h
decentralized**

code PP006L.940F/01

**PRODUCT DESCRIPTION**

Lighting fixtures with indoor track characterized by a sectional tube made of extruded aluminum 55 mm in diameter. Led cob cri>90. Color finish white. Degree of protection IP20. Decentralization version complete with cable length of 4000mm plus ceiling fixing element.

PRODUCT SPECS

Installation method	Mini Track
Light source	LED
Absorbed power	8 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Flood 24°
Finishing	White
Luminous flux of the product	1064 lm
Luminous efficiency	133 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Protocol	On/Off
Energy efficiency class	D
Weight	1.30 Kg
Dimension	H300 Ø55 mm
Power supply	220-240V 50-60Hz

WEB PAGE**ASSEMBLY
INSTRUCTIONS**

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 1