

**Mini Track - IPipedi 55/300h  
decentralized**

code PP119L.940WD/01

**PRODUCT DESCRIPTION**

Lighting fixtures with indoor track characterized by a sectional tube made of extruded aluminum 55 mm in diameter. Led cob cri>90. Color finish white. Degree of protection IP20. Decentralization version complete with cable length of 4000mm plus ceiling fixing element.

**PRODUCT SPECS**

|                              |                         |
|------------------------------|-------------------------|
| Installation method          | Mini Track              |
| Light source                 | LED                     |
| Absorbed power               | 12 W                    |
| Color temperature            | 4000K                   |
| Color rendering index CRI    | >90                     |
| Optic                        | Wide 36°                |
| Finishing                    | White                   |
| Luminous flux of the product | 1400 lm                 |
| Luminous efficiency          | 117 lm/W                |
| MacAdam color tolerance      | 2                       |
| Life time estimate           | 25000h L90 B10<br>ta25° |
| Protocol                     | Dimmable Dali           |
| Energy efficiency class      | D                       |
| Weight                       | 1.30 Kg                 |
| Dimension                    | H300 Ø55 mm             |
| Power supply                 | 220-240V 50-60Hz        |

**WEB PAGE****ASSEMBLY  
INSTRUCTIONS**

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 1