

## File Flex Circle 'O' Outdoor Diffuse Suspension

code FXG42.827/01





### PRODUCT DESCRIPTION

Outdoor circular suspension lamp made of extruded aluminium 6060, direct and diffused light emission, complete with LED 53 W, colour rendering index CRI>90. Transparent round power cable; steel suspension cables with millimetric regulator; Epoxy powder coating; Colour white. Protection class IP65.

### PRODUCT SPECS

|                           |                                 |
|---------------------------|---------------------------------|
| Light source              | LED                             |
| Absorbed power            | 53 W                            |
| Color temperature         | 2700K                           |
| Color rendering index CRI | >90                             |
| Finishing                 | White                           |
| MacAdam color tolerance   | 3                               |
| Life time estimate        | 3SDCM 50000h L90 B10<br>Ta 25°C |
| Energy efficiency class   | D                               |
| Weight                    | 3.9 Kg                          |
| Dimension                 | Ø800 mm                         |
| IP Grade                  | IP65                            |
| Power supply/Transformer  | Not included                    |
| Protocol                  | See power supply                |



### WEB PAGE



### ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 3

## OPTIONAL ACCESSORIES

### CANOPY CONNECTION



code LB420/01

REGISTERED DESIGN - File Flex is a versatile extruded aluminium profile, which can design infinite shapes. Its asymmetrical section is designed to realize unique lighting effects meanwhile ensuring optimal illumination levels. The linear LED source screened by a flexible opal extruded silicone diffuser creates seamless lighting effects. The system allows the use of blind modules, multi-optic from Leva series or adjustable spot from Spot Focus series Ø26 and Ø36. It has to be completed by stabilized drivers 24V or 48V.

Technical Sheet



