


File Flex Circle "O" outdoor Spot suspension

code FXG55.927S/01



PRODUCT DESCRIPTION

Circular outdoor ceiling light made of extruded aluminium 6060, direct light emission, complete with 40 LEDs 88 W, colour rendering index CRI>90. Transparent round cross-section power cable; steel suspension cables with millimetric adjuster; Epoxy powder coating; Micro textured white colour finish.

PRODUCT SPECS

Installation method	Suspension
Light source	LED
Absorbed power	40x2,2 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Spot 20°
Finishing	White
Luminous flux of the product	8600 lm
Luminous efficiency	98 lm/W
MacAdam color tolerance	3
Life time estimate	60.000H L80 B10
Energy efficiency class	D
Weight	7.9 Kg
Dimension	Ø1500 mm
IP Grade	IP65 / Ip66
Protection Class	Class III appliance

WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 1