


Ibrida wall 1800 3 spots and indirect

code IB033.940FD/01





PRODUCT DESCRIPTION

Lamp for wall h 1800 mm. Characterized by an extruded aluminum profile. Direct light, three spots, led line 17 W, ballast included. Color finish white. Protection class IP20.

PRODUCT SPECS

Installation method	Wall surface mounted
Light source	LED
Absorbed power	3x8 W / 17 W
Color temperature	4000K
Color rendering index CRI	>90
Optic	Flood 28°
Finishing	White
Luminous flux of the product	2116 lm
Luminous efficiency	88 lm/W
MacAdam color tolerance	2
Life time estimate	25000h L90 B10 ta25°
Protocol	Dimmable Dali
Energy efficiency class	D
Dimension	L40xW126xH1800 mm
IP Grade	IP20
Power supply	220-240V 50-60Hz



WEB PAGE



ASSEMBLY INSTRUCTIONS



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.
Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.
We reserve the right to make changes to our products at any time.

OPTIONAL ACCESSORIES

Ibrida Command Module



code IB100/01

Light switch and dimming accessory module that allows you to control the switching on, switching off and intensity of the light itself, directly on the product.

Technical Sheet



