

Manine outdoor diffused 90-V vertical single emission


code MN005P.940/01

30



120

100















Outdoor luminaire for indoor corner, single-emission for diffuse lighting. Complete optical unit with professional LED sources 6 W, complete with ballast. 90° internal angle version with 120x120 mm metal body, 30 mm wall projection white. Degree of protection IP54.

PRODUCT SPECS

Light source Lampadine Absorbed power 6 W Color temperature 4000K Color rendering index CRI >90 Finishing White Luminous flux of the product 150 lm Luminous efficiency 25 lm/W Life time estimate 3SDCM 50000h L80 B10 ta 25°C Weight 1.78 Kg Dimension L120xH120 mm IP Grade IP54	Installation method	Wall surface mounted
Color temperature 4000K Color rendering index CRI >90 Finishing White Luminous flux of the product 150 lm Luminous efficiency 25 lm/W Life time estimate 3SDCM 50000h L80 B10 ta 25°C Weight 1.78 Kg Dimension L120xH120 mm	Light source	Lampadine
Color rendering index CRI >90 Finishing White Luminous flux of the product 150 lm Luminous efficiency 25 lm/W Life time estimate 3SDCM 50000h L80 B10 ta 25°C Weight 1.78 Kg Dimension L120xH120 mm	Absorbed power	6 W
Finishing White Luminous flux of the product 150 lm Luminous efficiency 25 lm/W Life time estimate 3SDCM 50000h L80 B10 ta 25°C Weight 1.78 Kg Dimension L120xH120 mm	Color temperature	4000K
Luminous flux of the product 150 lm Luminous efficiency 25 lm/W Life time estimate 3SDCM 50000h L80 B10 ta 25°C Weight 1.78 Kg Dimension L120xH120 mm	Color rendering index CRI	>90
Luminous efficiency 25 Im/W Life time estimate 3SDCM 50000h L80 B10 ta 25°C Weight 1.78 Kg Dimension L120xH120 mm	Finishing	White
Life time estimate 3SDCM 50000h L80 B10 ta 25°C Weight 1.78 Kg Dimension L120xH120 mm	Luminous flux of the product	150 lm
Life time estimate ta 25°C Weight 1.78 Kg Dimension L120xH120 mm	Luminous efficiency	25 lm/W
Dimension L120xH120 mm	Life time estimate	
	Weight	1.78 Kg
IP Grade IP54	Dimension	L120xH120 mm
	IP Grade	IP54
Product Spec Square shape	Product Spec	Square shape
Power supply 220-240V 50-60Hz	Power supply	220-240V 50-60Hz

WEB PAGE



ASSEMBLY



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.