

Nyx Frame Directional TF111D for plasterboard

code NF070.935F/01
























PRODUCT DESCRIPTION

Round or square, fix or directional, trimless recessed downlight for ceiling installation, for accentor diffused lighting. Light source in recessed position for anti-glare lighting. Available both in plasterboard false-ceiling and in concrete/brick wall installation version. For integrated LED source or for 12V/230V QR-CB 35, QR-CB 51 and QR-LP 111 or 230V QPAR16 GU10 halogen/led lamps. Body and optical group in painted aluminum. Version with Integrated Chip On Board LED source provided with 99,99% pure aluminum coated reflector. Directional versions: optical group adjustable 355° horizontally and +/- 20° vertically. Remote power-supply available as an accessory. Degree of protection IP20/IP23/IP54.

PRODUCT SPECS

| Installation method | Recessed with frame |
|------------------------------|---------------------------------|
| Light source | LED |
| Absorbed power | 24,3 W / 32 W |
| Color temperature | 3500K |
| Color rendering index CRI | >90 |
| Optic | Flood 24° |
| Finishing | White |
| Luminous flux of the product | 2742 lm / 3551 lm |
| Luminous efficiency | 113 lm/W / 111 lm/W |
| MacAdam color tolerance | 3 |
| Life time estimate | 3SDCM 50000h L90 B10 ta 25°C |
| Energy efficiency class | E |
| Weight | 1.65 Kg |
| Dimension | H165 Ø160 mm |
| Hole size | 154 mm |
| IP Grade | IP20/54 |
| Protection Class | Class III appliance |
| Product Spec | Circular shape |
| Power supply/Transformer | Not included |
| Protocol | See power supply |
| | |

WEB PAGE



ASSEMBLY



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

OPTIONAL ACCESSORIES


Accessori Lens ø 111 Satin lens Ø 111



code L111S uncategorized




Accessori Lens ø 111 Elissoidal lens Ø 111



code L111E uncategorized




Accessori Lens ø 111 Asymmetric lens Ø 111



code L111A uncategorized



Accessori Lens ø 111 Honey cmb louver Ø 111



code L111R uncategorized



