

Nyx Tube T 35

code LTN30T.927F/01




















PRODUCT DESCRIPTION

Wall/ceiling recessed lamp, rpund section, direct light. Possibility to install total recessed or semi-recessed

PRODUCT SPECS

| Installation method | Recessed with frame |
|------------------------------|------------------------|
| Light source | LED |
| Absorbed power | 5 W |
| Color temperature | 2700K |
| Color rendering index CRI | >90 |
| Optic | Flood 22° |
| Finishing | White |
| Luminous flux of the product | 666 lm |
| Luminous efficiency | 133 lm/W |
| MacAdam color tolerance | 2 |
| Life time estimate | 50000h L90 B10 ta 25°C |
| Energy efficiency class | D |
| Dimension | H84/144 Ø40 mm |
| Hole size | Ø 65 mm |
| IP Grade | IP20/54 |
| Protection Class | Class III appliance |
| Product Spec | Circular shape |
| Power supply/Transformer | Not included |
| Protocol | See power supply |





NYX 35 TUBE LED 105° 105° cd/klm 90° 90° 75° 75° 60° 60° 1045 45° 45° 4180 η = 100 % 30° 15°

WEB PAGE







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.