

code LT7002.835S/01






















14° **MANINE LED** 105° cd/klm 90° 90°

75° 75° 60° 60° 45° 45° 485 5980 η = 100 % 30° 30°

PRODUCT DESCRIPTION

Indoor luminaire for outdoor corner, single-emission for Complete optical assembly with diffuse lighting. professional LED sources 3 W, complete with ballast. 270° outdoor corner version with 120x120 mm metal housing, 30 mm wall projection white. IP40 degree of protection.

PRODUCT SPECS

Installation method	Wall surface mounted
Light source	LED
Absorbed power	2x1,5 W
Color temperature	3500K
Color rendering index CRI	80
Optic	Spot 14°
Finishing	White
Luminous flux of the product	191 lm
Luminous efficiency	64 lm/W
MacAdam color tolerance	3
Life time estimate	50000h L80 B10 ta 25°C
Energy efficiency class	D
Weight	0.78 Kg
Dimension	L120xH120 mm
IP Grade	IP40
Power supply	220-240V 50-60Hz

WEB PAGE



ASSEMBLY



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.