

# Nyx Frame TF50F Fixed for plasterboard

code NF028/01

















#### PRODUCT DESCRIPTION

Recessed ceiling luminaire with round frame, with fixed optics for accent and diffuse lighting. Light source in back anti-glare position. Available in versions for plasterboard installation. With integrated LED source with 99.9% pure aluminium metallic reflector. Body and body in painted aluminum. Remote power available as an accessory. IP20/IP54. Insulation class III.

#### **PRODUCT SPECS**

Installation method	Recessed with frame
Light source	GU10
Absorbed power	50 W
Color rendering index CRI	Depending on the bulb (not included)
Optic	
Finishing	White
Luminous flux of the product	Depending on the bulb (not included)
Luminous efficiency	Depending on the bulb (not included)
Energy efficiency class	E-G
Dimension	mm
Hole size	70 mm
IP Grade	IP20/54
Product Spec	Circular shape
Power supply/Transformer	Not included
Protocol	See power supply

**WEB PAGE** 



**ASSEMBLY** 



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

#### **MANDATORY ACCESSORIES**

# AE350.16C (Copia)



code AE350.15C

Electronic power supply current

#### AE500.20C1




code AE500.20C1

Electronic power supply current

# **OPTIONAL ACCESSORIES**

#### Accessori Lens ø 50 Elissoidal lens Ø 50




code L050E

uncategorized Warning: Not suitable with halogen lamp

# Technical Sheet

# Accessori Lens ø 50 Asymmetric lens Ø 50




code L050A

uncategorized Warning: Not suitable with halogen lamp



# Accessori Lens ø 50 Honey comb Ø 50



code L050R

uncategorized

