

Mini Sight Frame 4

code MS40.935F/01




















PRODUCT DESCRIPTION


Square recessed fixture with frame, 4 lamps. Adjustable pull-out optic.

PRODUCT SPECS

Installation method	Recessed with frame
Light source	LED
Absorbed power	4x12 W / 4x18 W
Color temperature	3500K
Color rendering index CRI	>90
Optic	Flood 46°
Finishing	White
Luminous flux of the product	5400 lm / 6396 lm
Luminous efficiency	113 lm/W / 89 lm/W
MacAdam color tolerance	2
Life time estimate	2SCDM 50.000h L90 B10 ta25°
Protocol	On/Off
	On/On
Energy efficiency class	D
Energy efficiency class	D L207xW207xH135 Ø55
Energy efficiency class Dimension	D L207xW207xH135 Ø55 mm
Energy efficiency class Dimension IP Grade	D L207xW207xH135 Ø55 mm IP20
Energy efficiency class Dimension IP Grade Protection Class	D L207xW207xH135 Ø55 mm IP20 Class III appliance
Energy efficiency class Dimension IP Grade Protection Class Product Spec	D L207xW207xH135 Ø55 mm IP20 Class III appliance Square shape







WEB PAGE







Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.

MANDATORY ACCESSORIES

Box mini sight 4

81

code MSC04

Galvanized metal wallbox to be recessed in brick walls or reinforced concrete to fit MINI sight 4.



