

**File Flex sistema - Focus Ø36 File
Flex 24/48V**

code FX200.930ZD10/01



PRODUCT DESCRIPTION

REGISTERED DESIGN - File Flex is a versatile extruded aluminium profile, which can design infinite shapes. Its asymmetrical section is designed to realize unique lighting effects meanwhile ensuring optimal illumination levels. The linear LED source screened by a flexible opal extruded silicone diffuser creates seamless lighting effects. The system allows the use of blind modules, multi-optic from Leva series or adjustable spot from Spot Focus series Ø26 and Ø36. It has to be completed by stabilized drivers 24V or 48V.

PRODUCT SPECS

Installation method	system
Light source	LED
Absorbed power	8 W
Color temperature	3000K
Color rendering index CRI	>90
Optic	Asymmetric 18°x38°°
Finishing	White
Luminous flux of the product	508 lm
Luminous efficiency	64 lm/W
MacAdam color tolerance	3
Life time estimate	3SDCM 50000h L90 B10 Ta 25°C
Protocol	Dimmable 1-10V
Energy efficiency class	E
Weight	0.30 Kg
Dimension	H92 Ø36 mm
IP Grade	IP20
Protection Class	Class III appliance
Power supply/Transformer	Not included
Protocol	See power supply

WEB PAGE



**ASSEMBLY
INSTRUCTIONS**

