


Leva Quadra Mini Track Q4 24/48V trimless recessed

code LV321A.930SD/01



















PRODUCT DESCRIPTION

Fix and adjustable projectors family with chip on board LED sources. Mounting options: recessed, with frame or trimless, ceiling and wall-mounted and on 48V tracks, such as the Multi System by Stucchi. Fixture's body in painted extruded aluminum. Optical group complete with CRI>90 chip on board led, lens, antiglare housing and electronic driver (except for recessed versions). The optical group is fixed in the recessed version and adjustable (0-90° on the horizontal axis and 355° on the vertical axis) in the surfacemounted and track versions. Spot, flood and wide optics. UGR<19. Degree of protection IP20/40.

PRODUCT SPECS

| Installation method | Track |
|------------------------------|-------------------------|
| Light source | LED |
| Absorbed power | 4x2,2 W |
| Color temperature | 3000K |
| Color rendering index CRI | >90 |
| Optic | Spot 20° |
| Finishing | White box - black optic |
| Luminous flux of the product | 800 lm |
| Luminous efficiency | 91 lm/W |
| MacAdam color tolerance | 3 |
| Life time estimate | 60.000H L80 B10 |
| Protocol | Dimmable Dali |
| Energy efficiency class | D |
| Weight | 0.60 Kg |
| Dimension | L68x68xW139xH118 mm |
| IP Grade | IP20 |
| Power supply/Transformer | Not included |
| Protocol | See power supply |
| | |

WEB PAGE



ASSEMBLY



Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres. Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified. We reserve the right to make changes to our products at any time.