


**File Pro System - Suspension
modules**

code FP026.927SAD/01

**PRODUCT DESCRIPTION**

Modular system, in extruded aluminum 98x48mm, suspended or on electrified three-phase track to be completed with the necessary dedicated accessories. Embossed painted finish. Screens for diffused light in opal polycarbonate, professional optics with different beam openings. They might be equipped, if necessary, with soundabsorbing panels in different colors and materials. IP

Dimmable Dali / Touch & Dimm

PRODUCT SPECS

Installation method	system
Light source	LED pro
Absorbed power	82 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Single asym
Finishing	White
Luminous flux of the product	12500 lm
Luminous efficiency	152 lm/W
MacAdam color tolerance	3
Life time estimate	3SDCM 50000h L90 B10 Ta 25°C
Protocol	Dimmable Dali / Touch & Dimm
Energy efficiency class	D
Weight	4.7 Kg
Dimension	L98xW1430xH48 mm
IP Grade	IP20
Power supply	220-240V 50-60Hz

WEB PAGE**ASSEMBLY
INSTRUCTIONS**

Complies with EN605981 and related notes. In the absence of metric symbols, the measurements are all in millimetres.

Luminous flux and power data are initially subject to tolerances +/- 10%. The values refer to an ambient temperature of 25°C unless otherwise specified.

We reserve the right to make changes to our products at any time.

Page 1 / 1