

Optical group Leva Q4 Outdoor

code LV351K.927F/01






















PRODUCT DESCRIPTION

Recessed with frame outdoor fixture, complete of 4x led 2,2 w beam 32°, color rendering index>90. White finishing

To be completed with remote driver

PRODUCT SPECS

Installation method	Recessed with frame
Light source	LED
Absorbed power	4x2,2 W
Color temperature	2700K
Color rendering index CRI	>90
Optic	Flood 32°
Finishing	White
Luminous flux of the product	860 lm
Luminous efficiency	98 lm/W
MacAdam color tolerance	2
Life the ended to	E00001 T 050100D40
Life time estimate	50000h Ta 25° L90B10
Protocol	On/Off
Protocol	On/Off
Protocol Energy efficiency class	On/Off E
Protocol Energy efficiency class Weight	On/Off E 0.2 Kg
Protocol Energy efficiency class Weight Dimension	On/Off E 0.2 Kg L61xW61xH33 mm
Protocol Energy efficiency class Weight Dimension Hole size	On/Off E 0.2 Kg L61xW61xH33 mm 34x96 mm
Protocol Energy efficiency class Weight Dimension Hole size IP Grade	On/Off E 0.2 Kg L61xW61xH33 mm 34x96 mm Ip56
Protocol Energy efficiency class Weight Dimension Hole size IP Grade Protection Class	On/Off E 0.2 Kg L61xW61xH33 mm 34x96 mm lp56 Class III appliance

WEB PAGE



MANDATORY ACCESSORY ACCORDING TO THE TYPE OF INSTALLATION

Accessori Wallbox Q4 box frame




code LV301F/01

Recessed with frame uncategorized wallbox for false ceiling. Bianco finishing wallbox for false ceiling



Accessori Wallbox Q4 box minimal



code LV301M

Trimless recessed uncategorized wallbox for false ceiling



MANDATORY ACCESSORIES

AE700.10C



code AE700.10C

Electronic power supply current